

Features

Super Smooth & **Grey Back**

Prevents light transparency and shadowing

The material does not require lamination

Matte & Glossy surface available

Best suited for pop-up, roll-up, x-displays and an array of close viewing indoor applications

Applications



Technical Data Sheet

Item Code		PT801	Test Method
Support Cloth		Polyethylene Terephthalate	DIN EN ISO2060
Weight (GSM)		440	DIN EN ISO2286-2
Thickness (MM)		0.30	---
Tensile Strength	Warp (N/5cm)	1200	ISO527/3:1995
	Weft (N/5cm)	1400	ISO527/3:1995
Tear Strength	Warp (N/5cm)	3.6	ISO4674/1:2003
	Weft (N/5cm)	3.5	ISO4674/1:2003

Information contained in this document is based on our general experience and is given in good faith. But we are unable to accept responsibility in respect to factors which are outside our knowledge or control.

Ink Printability

SOLVENT	ECO-SOLVENT	UV	LATEX	SCREEN PRINTING
■	■	■		



Add: Room 912, No.3 Building, Shangdong Business Center, Haizhou District,
Haining, Zhejiang, China
Tel: +86-573-80776996 Fax: +86-573-80776998
Mob/Skype/Wechat: +86-15858322153
mailto:hncomax@163.com jeffcheung@hncomax.com

